



PROFESSIONAL AUDIO PRODUCTS

100V Line PA Speakers
F/E 100mm C 2101C

DESCRIPTION

This quality loudspeaker forms the backbone of public address and background music systems. The driver incorporates a TDK magnet and dual cone construction for extended frequency response. The line transformer is multi-tapped and is wound on high grade silicon steel. This results in a high efficiency, wide range 100V line speaker capable of meeting the demands of professional public address applications. Also equipped with a 4 way wire protect terminal & 22uf bipolar capacitor to meet relevant Australian standard. The unique safety cover protects the exposed terminals of the 100V line transformer from installer and prevents short circuits to building structure eg: air conditioning ducting. It is a registered Altronic design.



FEATURES

- Dual cone construction for extended high frequency response
- Outstanding sound reproduction
- TDK speaker magnet
- 5W multi-tapped 100V line transformer fitted
- Emergency evacuation models available
- Suits REDBACK speaker grills
- Features the Redback transformer safety cover

SPECIFICATIONS*

MODEL: **C 2101C**
Power Taps: 0.33, 0.66, 1.25, 2.5, 5W
Rated Power: 5W
SPL: 90dB, 1W @ 1m
Freq. Resp.: 100Hz - 20kHz
Weight: ≈ 700g
Dimensions: ≈ 100mmØ x 105mmH
Cutout Dimensions: ≈ 85mmØ

* Specifications subject to change without notice.

Distributed By: